TPI CORPORATION

America's Comfort Conditioning Company

2021 SUMMER SALE

© Copyright 2020; TPI Corporation | 1-800-682-3398 | 1-423-477-4131 | www.tpicorp.com | answers@tpicorp.com

HIGH VELOCITY SUSPENSION BLOWERS DIRECT DRIVE

Housing design provides directional high velocity air flow for all types of indoor air circulating applications

2 YEAR WARRANTY

ETL LISTED c US — Intertek

MOTOR: 120V, direct drive, totally enclosed, single phase, ball bearing, permanently lubricated, Class B rating
BLADE: Steel hub, spider and 3 aluminum paddles
CORD: None, hard wire connection only
GUARD: OHSA approved spiral steel wire black coated (front & rear)
POLE: 1-speed, non-oscillating fan head

SINGLE SPEED FAN MOTORS / HARD-WIRED CONNECTION (No Cord) SHIPS FULLY ASSEMBLED

MODELS	BLADE SIZE	TYPE	MOTOR HP	VOLTS	CFM	COVERAGE AREA SQ.FT	AMPS	PRICE EACH
HV18-120V	16”	Direct Drive	1/2	120	5,000	175	3.4	$693.00
HV24-120V	22”				8,500	275	3.8	$794.20
HV30-120V	28”		1		14,250	375	7.6	$1,147.85

HV SERIES

PROUDLY DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

Accessories:

MODELS	TYPE (Fits Models)	PRICE EACH
HV-1	Dock arm (HV18 only)	$101.20
HV-2	Wall/Column (HV18/24)	$144.65
HV-3	Wall/Column (All)	$150.15

HV-1 Dock Arm Mount Accessory plus HV-18 Fan

HV-2 OR HV-3 Wall/Column Mount Accessory plus HV-30 Fan Head

Meets Federal OSHA Requirements / 2 Year LIMITED Warranty

PORTABLE BLOWERS DIRECT DRIVE

MOTOR: 120V, single phase, totally enclosed, sleeve-bearing, permanently lubricated, PSC type
SWITCH: Rocker switch
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral coated steel wire, black finish - OSHA approved
WHEELS: 8” rubber (30/36”), 10” (42”); all models 1” thick
HOUSING: Corrosion & dent resistant high density polyethylene black housing
SPEED: 2-speed (42” is single speed)

PBX-D SERIES

PROUDLY DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

ETL LISTED c US — Intertek

MODELS	BLADE SIZE	MOTOR TYPE	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
PBX 30-D	30”	Direct Drive	1/4	7,200	250	2.5	$405.90
PBX 36-D	36”		1/3	11,500	320	5.5	$454.85
PBX 42-D	42”		1/2	15,000	340	6.0	$592.35

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

30” INDUSTRIAL AIR CIRCULATOR HIGH PERFORMANCE 1/3 HP, 120V

FAN HEAD ASSEMBLED AT FACTORY TO SIMPLIFY INITIAL SETUP

IHP SERIES

MOTOR: 2-Speed, 1/3 HP, 120V, single phase, totally enclosed (TEAO), ball bearing, PSC type
BLADE: Steel hub, spider, with aluminum paddles
SWITCH: Pull Chain
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral steel wire coated (front & rear)
POLE: Pedestal pole adjusts center of fan from 48” - 67”

High performance 1/3 HP motor runs 15% - 18% cooler than standard 1/4 HP motors & allows fan to continue operating in air temperatures up to 135°F

FAN HEAD (IHP30-H) $315.70

PEDESTAL (ACM-P) $129.80

WALL MOUNT (ACM-W) $50.05

I-BEAM MOUNT (ACM-I) $98.45

CEILING MOUNT (ACM-C) $64.90

MODEL	BLADE SIZE	MOTOR TYPE	FAN TYPE	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
IHP 30-H	30”	Totally Enclosed	Non-Oscillating	1/3	7,200	250	3.0	$315.70

Must order fan head and mount separately

3 Year Motor Warranty

24” & 30” INDUSTRIAL AIR CIRCULATORS OSCILLATING & NON-OSCILLATING 1/4 HP, 120V

ALL FAN COMPONENTS SHIPPED UNASSEMBLED IN ONE CARTON

ACU SERIES

ACU 30-P

ACU 30-WO

MOTOR: 2-Speed, 1/4 HP, 120V, single phase, totally enclosed (TEAO), ball bearing, PSC type
BLADE: Steel hub, spider, with aluminum paddles
SWITCH: Pull Chain
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral steel wire coated (front & rear)
POLE: Pedestal pole adjusts center of fan from 48” - 67”

Oscillates horizontally in a 90° arc or can be locked in a fixed position

Metal gears in the oscillating mechanism allow the fan to operate at a maximum 30° downward tilt

MODELS	BLADE SIZE	MOTOR TYPE	FAN TYPE	FAN MOUNT	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
ACU 24-P	24”	Totally Enclosed	Non-Oscillating	Pedestal	1/4	6,000	240	2.5	$304.15
ACU 30-P	30”					7,200	250	2.7	$312.95
ACU 24-W	24”			Wall		6,000	240	2.5	$253.55
ACU 30-W	30”					7,200	250	2.7	$262.90
ACU 30-PO	30”		Oscillating	Pedestal	1/4	6,000	240	2.5	$471.35
ACU 30-WO				Wall		7,200	250	2.7	$395.45

Models include fan motor, grills, and mount in one carton

1 Year Motor Warranty

© Copyright 2020; TPI Corporation | 1-800-682-3398 | 1-423-477-4131 | www.tpicorp.com | answers@tpicorp.com

30” INDUSTRIAL AIR CIRCULATOR HEAVY DUTY - SAFETY YELLOW 1/2 HP

FAN HEAD ASSEMBLED AT FACTORY TO SIMPLIFY INITIAL SETUP

HDH SERIES

MOTOR: 2-Speed, 1/2 HP, 120V, single phase, totally enclosed (TEAO), ball bearing, PSC type
BLADE: Steel hub, spider, with aluminum paddles
SWITCH: Pull Chain
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral steel wire coated (front & rear)
POLE: Pedestal pole adjusts center of fan from 48” - 67”

5 YEAR WARRANTY

Intertek

PROUDLY DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

FAN HEAD (HDH 30) $422.40

PEDESTAL (HDM-P) $137.50

SAFETY YELLOW COLOR

Must order fan head and mount separately

MODEL	BLADE SIZE	MOTOR TYPE	FAN TYPE	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
HDH 30	30”	Totally Enclosed	Non-Oscillating	1/2	8,000	270	4.0	$422.40

Meets Federal OSHA Requirements / 5 Year Motor Warranty

30” INDUSTRIAL AIR CIRCULATOR HEAVY DUTY - SAFETY YELLOW 1/2 HP

FAN HEAD ASSEMBLED WITH DROP-DOWN SWITCH & HINGED GUARD

HDH-JR SERIES

MOTOR: 2-Speed, 1/2 HP, 120V, single phase, totally enclosed (TEAO), ball bearing, PSC type
BLADE: Steel hub, spider, with four aluminum paddles
SWITCH: Drop-down switch; 18” long
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral steel wire coated with hinged guard
MOUNT: Fan head can be mounted to pedestal or wall mounting bracket.

5 YEAR WARRANTY

Intertek

PROUDLY DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

FAN HEAD (HDH-30-JR) $463.10

LOW/HIGH & OFF SWITCH

SAFETY YELLOW COLOR

WALL MOUNT (HDM-W) $55.00

Must order fan head and mount separately

MODEL	BLADE SIZE	MOTOR TYPE	FAN TYPE	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
HDH 30-JR	30”	Totally Enclosed	Non-Oscillating	1/2	8,000	270	4.0	$463.10

Meets Federal OSHA Requirements / 5 Year LIMITED WARRANTY

PORTABLE BLOWERS - BELT DRIVE

MOTOR: 120V, single-phase, totally enclosed, sleeve-bearing, permanently lubricated, PSC type
SWITCH: Rocker switch
CORD: 12’ long SJT type 3 conductor
GUARD: Spiral coated steel wire, black finish - OSHA approved
WHEELS: 10” diameter rubber wheels, 1” thick (8” dia. on PBX-36B)
HOUSING: Corrosion & dent resistant high density polyethylene black housing
BLADE: 4-paddle aluminum; 48” model contains steel blade
SPEED: Single speed

Belt drive blowers provide higher CFM & operate quieter than direct drive units!

PROUDLY DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

Intertek

PBX-D SERIES

IMPROVES AIR QUALITY

MODELS	BLADE SIZE	MOTOR TYPE	MOTOR HP	CFM MAX. VELOCITY	COVERAGE AREA SQ.FT.	AMPS	PRICE EACH
PBX 36-B	36”	Belt Drive	1/2	14,000	360	8.0	$589.60
PBX 42-B	42”		3/4	17,500	420	11.0	$706.75
PBX 48-B	48”		1	23,500	550	15.0	$781.00

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

INDUSTRIAL SHUTTER MOUNTED EXHAUST FANS

Shutter mounted fans install on side wall & eliminate the need for external framing

CE-DS SERIES

DESIGNED, ENGINEERED, TESTED, ASSEMBLED IN THE USA

MOTOR: 120V, 1-Phase, totally enclosed, permanently lubricated
- 1/12 HP motor is 3-Speed sleeve bearing permanent split capacitor
- 1/8 HP motor is 3-Speed sleeve bearing permanent split capacitor
- 1/4 HP motor is 2-Speed ball bearing permanent split capacitor

BLADE: 3-Paddle aluminum blade
SWITCH: Pull chain
CORD: No cord – junction box provided for direct wiring
GUARD: Spiral steel wire coated
SHUTTER: Aluminum louvers & steel frame design for gravity close direct airflow
Includes weather stripping for tighter seal

MODELS	BLADE SIZE	MOTOR TYPE	MOTOR BEARING	MOTOR HP	CFM			AMPS	PRICE EACH
					HIGH	MEDIUM	LOW		
CE 12-DS	12”	Totally Enclosed	Sleeve	1/12	825	710	560	1.1	$238.70
CE 14-DS	16”			1/8	2,100	1,900	1,700	2.1	$301.95
CE 18-DS	18”				2,300	2,100	1,850	2.2	$343.20
CE 20-DS	20”		Ball	1/4	2,925	N/A	2,380	2.3	$407.00
CE 24-DS	24”				3,400	N/A	2,770	2.5	$452.10
CE 30-DS	30”				3,950	N/A	3,080	2.7	$566.50

Shutter frame includes weather stripping for tighter seal & year-round unit protection.

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

LOADING DOCK FAN & OPTIONAL LIGHT HEAD

LDF-TE SERIES

ARM: 1 ½” square, triple-arm strut, 14-gauge steel tubing
FINISH: Chip resistant safety yellow & black powder coated
CORD: 5’ long SJT type 3 conductor
FAN: 18” all metal fan with 3-speed, 1/8 HP, PSC totally enclosed motor, 2.2A, 120V

40” DOCK ARM REACH

LIGHT HEAD TYPE	MAX WATTS	MAX LUMENS	AVG BULB LIFE (HRS)	INCLUDED	
				BULB	GUARD
No Bulb	300	3,700	2,000	No	Yes
LED	37	12,373	30,000	Yes	No

Intertek

Light head sold separately

40-LDF-TE
(40” Arm & 18” Fan Head)
$262.35

DKL-INC
(No Bulb)
$53.90

DKL-LED-37
(LED)
$216.15

Meets Federal OSHA Requirements / 1 Year LIMITED WARRANTY

HIGH EFFICIENT CEILING FANS

Indoor or Outdoor Applications

E-CF SERIES

Intertek

- 120-volt / single phrase
- ETL listed for USA & China
- Includes 24” stainless steel safety cable kit
- Permanently sealed double radial ball bearing PSC motor
- All white powder coated finish; blade, motor and downrod
- Polymer 3-paddle blades designed for quiet operation
- Easy to mount to supplied steel J-Hook connection
- Satisfies the U.S. Department of Energy’s “Energy Guide” requirements
- E56-CF (85-Watt) & E60-CF (90-Watt) models contain:
  a. (4) 24” lg. lead wires, forward/reverse direct wiring option for downflow direction; requires remote switch - recommend using model **KBWC-15SK** for variable & directional speed control.
  b. 18” downrod

56” Reversible
Moisture Rated
(E56-CF)
$140.80

60” Reversible
Moisture Rated
(E60-CF)
$173.25

E60-CFC

60” Down Draft
IP65 Outdoor Rated
Cord & Controller
95-watt
(E60-CFC)
$272.25

Variable Speed & Switch Controller up to 5 Fans

(KBWC-15SK)
$101.75

IMPROVES AIR QUALITY

DISTRIBUTED BY:

Note: Prices subject to change without notice

© Copyright 2020; TPI Corporation | 1-800-682-3398 | 1-423-477-4131 | www.tpicorp.com | answers@tpicorp.com