

Paintstik Markers



B Paintstik®

- Marks on any material, surface or texture.
- Real paint in stick form.
- Weather-resistant, UV-resistant.
- Ideal for layout, color coding, fabrication and identification.
- Marks through oil and water.
- Marks on smooth, rough, rusty or dirty surfaces.
- For use on metal, wood, plastic, concrete, rubber, glass, cardboard and paper.
- Lead-free, non-toxic.
- Available in 3 sizes.
- B & B-1" Unit packaging: 12 of one color to a box.
- B-3/8" Unit packaging: 36 of one color to a box.

Size: 11/16" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C)

| Color | Standard Part No. | B-3/8" Part No. | B-1" Part No. | Standard Carded ¹ |
|-------------|-------------------|-----------------|---------------|------------------------------|
| White | 80220 | 80420 | 80260 | 80200 |
| Yellow | 80221 | 80421 | 80261 | 80201 |
| Red | 80222 | 80422 | | |
| Black | 80223 | 80423 | | |
| Orange | 80224 | | | |
| Blue | 80225 | 80425 | | |
| Green | 80226 | 80426 | | |
| Pink | 80227 | | | |
| Purple | 80228 | | | |
| Brown | 80229 | | | |
| Gray | 80230 | | | |
| Gold | 80231 | | | |
| Aluminum | 80232 | | | |
| Flr. Yellow | 82821 | | | |

Standard Case Quantity: 144

¹Carded: 2 per card, 36 cards per case



B-E Paintstik® Marker

- Real paint in stick form.
- For marking rough surfaces, forgings, castings, lumber and concrete.
- Marks will withstand prolonged immersion in water.
- Lead-free, non-toxic.
- Long lasting, weather-resistant, fade-resistant.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C).

| Color | Part No. |
|--------|----------|
| White | 80620 |
| Yellow | 80621 |
| Red | 80622 |
| Black | 80623 |
| Orange | 80624 |
| Blue | 80625 |
| Green | 80626 |

Case Quantity 144



E Paintstik® Marker

- Real paint in stick form.
- High intensity colors.
- For greater visibility in dimly lit areas.
- For coding, identification, layout and fabricating work.
- Long-lasting, weather-resistant, fade-resistant.
- Available in regular and king size.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4" and 1" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C).

| Color | Part No. |
|--------|----------|
| White | 88620 |
| Yellow | 88621 |
| Orange | 88624 |
| Blue | 88625 |

Case Quantity 144



BL Paintstik® Marker

- Real paint in stick form.
- Bleeds through solvent or oil-based paints.
- For fabricating structural steel, or layout work where the marks are required to bleed through a primer coat covering the marks.
- To prevent bleeding through the finish coat, seal the marked areas with waterbased epoxy paint.
- Unit packaging: 12 to a box.

Size: 11/16" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C).

| Color | Part No. |
|-------|----------|
| Blue | 80725 |

Case Quantity 144



F Paintstik® Fluorescent Marker

- Real paint in stick form.
- Ultra high visibility fluorescent colors.
- For marking metal, wood, glass, concrete, rubber, cardboard, and paper.
- Marks through oil and water
- Ideal for layout, inspection, and color coding.
- Glows under a black light.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C).

| Color | Part No. |
|--------|----------|
| Yellow | 82831 |
| Red | 82832 |
| Orange | 82834 |
| Blue | 82835 |
| Green | 82836 |
| Pink | 82842 |

Case Quantity 72



Fast Dry Paintstik® Marker

- Real paint in stick form.
- Marks dry in 5 minutes.
- Ideal for marking in fabricating shops and assembly lines where immediate handling is necessary.
- For marking metal, wood, glass, plastic, concrete, rubber, cardboard, and paper.
- 3/8" size available.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4" & 3/8" x 4-1/4"

Marking range: -50°F to 150°F (-46°C to 66°C).



N Paintstik® Marker

- Real paint in stick form, dries overnight.
- Marks will not show through top coat of primer or finish layer of paint.
- Ideal for shipbuilding or other metal fabrication that will be given a final coat of paint.
- For marking metal, wood, glass, plastic, concrete, rubber, cardboard, and paper.
- Will mark on wet, dry, rusty, icy, smooth and/or rough material.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4"

Marking range: 0°F to 150°F (-18°C to 66°C)



M & M-10 Paintstik® Markers

- Real paint in stick form.
- Marks withstand annealing and heat treating operations.
- For welds, ingots, castings, forgings, and annealed parts.
- Will not come off in oil or water baths.
- Unit packaging: 12 of one color to a box.

Size: 11/16" x 4-3/4"

Mark at room temperature

M withstands 1600°F (871°C)

M-10 withstands 1800°F (982°C)



P Paintstik® Marker

- Real paint in stick form, non-drying.
- For marking steel prior to galvanizing process.
- Marks are completely removed in the pickling bath and will not interfere with the galvanizing process.
- Unit packaging: 12 to a box.

Size: 11/16" x 4-3/4"

Marking range: -50°F to 150°F (-46°C to 66°C).



WS 3/8" Paintstik® Marker

- Water soluble for easy removal.
- Smaller diameter for finer line marking.
- Ideal for the temporary marking of plastics, glass, painted metal surfaces, polished aluminum, car bumpers, and exotic metals.
- Unit packaging: 36 of one color to a box.

Size: 3/8" x 4-1/4"

Marking range: -50°F to 150°F (-46°C to 66°C).

| Marker | Color | Part No. |
|--|------------------|----------|
| Fast Dry Paintstik Case Quantity 72 | White | 82720 |
| | Yellow | 82721 |
| | Red | 82722 |
| | Black | 82723 |
| | 3/8" Size White | 82730 |
| | 3/8" Size Yellow | 82731 |
| M Paintstik Case Quantity 144 | White | 81920 |
| | Yellow | 81921 |
| | Red | 81922 |
| | Black | 81923 |
| M-10 Paintstik | White | 82020 |
| WS 3/8" Paintstik Case Quantity 144 | White | 82420 |
| | Yellow | 82421 |
| | Red | 82422 |
| | Black | 82423 |
| N Paintstik Case Quantity 144 | White | 82120 |
| | Yellow | 82121 |
| | Red | 82122 |
| | Black | 82123 |
| P Paintstik Case Quantity 144 | White | 83420 |



Quik Stik® Marker

- Smooth marking, fast drying paint marks dry in 5-7 minutes.
- Bright, bold fade resistant colors.
- More marks for the money, 20% longer than other brands.
- Plastic holder with self-storing cap prevents breakage, keeps hands and clothing clean.
- Stick advances by turning twist-up knob.
- Marks on virtually any surface. Metal, glass, plastic, wood, cardboard, paper, etc.

Marking range: -50°F to 150°F (-46°C to 66°C)

| Color | Part No. | Case Qty. | Color | Part No. | Case Qty. |
|--------|----------|-----------|----------|----------|-----------|
| BULK | | | DISPLAY | | |
| Red | 61049 | 72 | Red | 61054 | 24 |
| Black | 61050 | 72 | Black | 61055 | 24 |
| White | 61051 | 72 | White | 61057 | 24 |
| Yellow | 61053 | 72 | Yellow | 61058 | 24 |
| Green | 61069 | 72 | Assorted | 61060 | 24 |
| Blue | 61070 | 72 | | | |
| Orange | 61071 | 72 | | | |
| Purple | 61073 | 72 | | | |
| CARDED | | | | | |
| Red | 61063 | 24 | | | |
| Black | 61064 | 24 | | | |
| White | 61067 | 24 | | | |
| Yellow | 61068 | 24 | | | |

Unit packaging:
Bulk - 12 of one color to a box
Carded - 1/Card
Assorted includes - 8 white, 4 black,
8 yellow and 4 red

Paintstik Markers / Chalk / Crayons / Tape

Hot Surface Paintstik Markers

H Paintstik® Marker

- Real paint in stick form.
- Bright colors for higher visibility.
- Mark hot coils, billets, slabs, bars, ingots, etc.
- Marks will not run, char, discolor, peel or crack.
- Marks are weather and fade-resistant.
- Unit packaging: 144 of a single color to a case.

| Color | Part No. |
|--------|----------|
| White | 81020 |
| Yellow | 81021 |
| Red | 81022 |
| Black | 81023 |
| Blue | 81025 |
| Green | 81026 |
| Brown | 81029 |

Size: 3/8" x 4-5/8"
Marking range: 150°F to 1200°F (66°C to 649°C)
Case Quantity 144

HT & HT-34 Paintstik® Marker

- Real paint in stick form.
- Bright colors for higher visibility.
- Mark very hot coils, billets, slabs, bars, ingots, etc.
- Marks will not run, char, discolor, peel or crack.
- Marks are weather and fade-resistant.
- Available in two sizes, regular and king size.
- HT & HT-34 unit packaging: 144 of a single color to a case plus 1-#100 holder.

| Color | HT Standard Part No. | HT King Part No. | HT-34 Standard Part No. | HT-34 King Part No. |
|--------|----------------------|------------------|-------------------------|---------------------|
| White | 81220 | 81210 | 84720 | 84710 |
| Yellow | 81221 | N/A | N/A | N/A |
| Red | 81222 | N/A | N/A | N/A |
| Black | 81223 | N/A | N/A | N/A |
| Blue | 81225 | N/A | N/A | N/A |
| Green | 81226 | N/A | N/A | N/A |

Case Quantity 144

HT Paintstik Size 3/8" x 4-1/2" Standard
 3/4" x 4-5/8" King
Marking range: 250°F to 1600°F (121°C to 871°C)

HT-34 Paintstik Size: 3/8" x 4-1/2" Standard
 3/4" x 4-5/8" King
Marking range: 400°F to 1800°F (204°C to 982°C)

Railroad Chalk



Size: 1" x 4"

Railroad Chalk

- Ideal for making temporary marks on most surfaces.
- Marks on metal, wood, concrete, cardboard, rubber, plastic, etc.
- The easy-to-hold 4" x 1" tapered shape makes broad, easy-to-read marks.
- Unit packaging: 144 per box. Packed 4 one gross boxes per case to prevent breakage during shipping.

| Color | Part No. |
|--------|----------|
| White | 80500 |
| Yellow | 80501 |
| Red | 80502 |
| Blue | 80505 |
| Green | 80506 |

Lumber Crayons



Size: 1/2" x 4-5/8"
Marking range:
-50°F to 150°F (-46°C to 66°C).

Lumber Crayon #500

- Also known as layout chalk or keel.
- Longer lasting than ordinary crayons.
- Makes weather resistant, water resistant marks.
- Lead free.
- Marks on concrete, wood, metal, plastic, rubber, paper, cardboard and ceramics.
- Fluorescent colors work well with computerized cut-off saws.
- Standard 1/2" hex. shape fits the #109 Peterson holder, #106 holder and #108 holder.
- Other colors available on request.
- Unit packaging: 12 of one color to a box.

| Color | Part No. |
|--------|----------|
| White | 80320 |
| Yellow | 80321 |
| Red | 80322 |
| Black | 80323 |
| Orange | 80324 |
| Blue | 80325 |
| Green | 80326 |
| Pink | 80327 |
| Purple | 80328 |
| Brown | 80329 |

Case Quantity 144

Duct Tape



Duct Tape

- Individually shrink wrapped for longer shelf life.
- Silver-grey color blends well with duct work.
- Quality construction resists breakdown from heat and moisture.
- Cotton blend cloth backing for better laminating strength.
- Tears straight, edges do not curl.

| Part No. | Size |
|----------|-------------|
| 44099 | 2" x 60 yds |

Case Quantity 24

Fiber Tip Markers



Dura-Ink® #15 Marker

- Ideal for fine line marking.
- Extra tough tip, won't spread or mush.
- Smear-resistant, water-resistant, fast drying.
- Marks on metal, wood, cardboard, paper, plastic, glass, etc.
- For identification of parts, layout work and marking cartons and crates.
- Available on blister card for point-of-purchase display.



Dura-Ink® #20 Marker: Medium Size

- Large ink supply for more mileage.
- Water resistant, fade-resistant, high intensity ink.
- Chisel tip makes fine lines or broad marks.
- Heavy-duty metal barrel.
- Use on cardboard, ceramics, wood, metal, rubber and glass.
- For identification of equipment, marking shipping cartons and making signs.



Dura-Ink® #25 Marker: King Size

- Chisel tip makes fine line or broad marks.
- Extra large ink supply for greater mileage.
- Heavy-duty metal barrel.
- Use on cardboard, wood, metal, paper, ceramics, glass, and leather.
- For identification of equipment, marking shipping cartons and making signs.

| Color | Dura-Ink #15 Part No. | Dura-Ink #20 Part No. | Dura-Ink #25 Part No. |
|--------------------|-----------------------|-----------------------|-----------------------|
| Yellow | | | 96221 |
| Red | 96022 | 96122 | 96222 |
| Black | 96023 | 96123 | 96223 |
| Blue | 96025 | | 96225 |
| Green | 96026 | | 96226 |
| Black ¹ | 96030 | | |
| Black ² | 96033 | | 96233 |

Unit packaging: 12 of one color to a box
Dura-Ink #15 Case Quantity: 72
Dura-Ink #20 & #25 Case Quantity: 48

1 = Packed in a display box
2 = Carded-1 per card

Meet U.S. Fed Spec. TT-I-544

Fineline Metal Markers



Red-Riter® Metal Marker

- Fine line marker for all types of metal surfaces.
- Marks won't rub off like soapstone.
- High visibility on aluminum and stainless steel.
- No sharpening necessary.



Silver-Streak® Metal Marker

- Available in original flat and NEW round sizes.
- Ideal for doing metal layout and fabrication work.
- Marks on all types of metal surfaces.
- Marks won't rub off like soapstone.
- Durable metal and plastic holders prevent breakage.
- Holders include pocket clip.

| Part No. | Shape | Case Qty. |
|----------|---------|-----------|
| 96005 | Flat | 24 |
| REFILLS | | |
| 96019 | 25 Pack | 24/case |
| HOLDERS | | |
| 96017 | 10 Pack | 12/case |

| Part No. | Shape | Case Qty. |
|----------|---------------|-----------|
| 96004 | Flat | 24 |
| 96006 | Round | 24 |
| REFILLS | | |
| 96018 | Flat, 25 pk. | 24 |
| 96002 | Flat, 100 pk. | 24 |
| 96007 | Round, 6 pk. | 24 |
| HOLDERS | | |
| 96017 | Flat, 10 pk. | 12 |

Trades Marker®



- Marks on plastic, glass, metal, wood, cardboard and paper.
- Marks won't rub off and are weather-resistant.
- Push-button holder advances the stick as needed.
- Needs no sharpening, eliminates the hassles found with the old paper wrapper china markers.
- Handy pocket clip keeps it in your pocket.
- Available in 5 bright colors.

| Part No. | Color | Case Qty. |
|----------|-----------------------------------|-----------|
| 96000 | 1 holder & 5 refills ¹ | 24 |
| REFILLS | | |
| 96009 | Orange, 6 pk. | 24 |
| 96042 | White, 6 pk. | 24 |
| 96043 | Yellow, 6 pk. | 24 |
| 96044 | Black, 6 pk. | 24 |
| 96045 | Red, 6 pk. | 24 |

¹ Contains 1 each of orange, white, black, yellow and red.

Liquid Paint Markers / Cool Gel / Bloc-It



Ball Paint Marker®

- Marks with real paint, dries in 5 minutes.
- Durable metal ball tip marks on smooth or rough surfaces.
- Marks on metal, wood, plastic, glass, any hard surfaces.
- Lead free, non-toxic.
- Marks are weather and fade-resistant.
- Unbreakable plastic bottle with 1/8" steel ball tip.
- Stores in pocket for easy access.
- Plastic cap keeps tip clean between jobs.
- Unit packaging: 12 of one color to a box.

Marking Range: -50°F to 150°F (-46°C to 66°C)

| Color | Part No. |
|---------------------|----------|
| White ¹ | 84600 |
| Yellow ¹ | 84601 |
| White | 84620 |
| Yellow | 84621 |
| Red | 84622 |
| Black | 84623 |
| Orange | 84624 |
| Blue | 84625 |
| Green | 84626 |

¹=carded -1/card

Carded items, Case Qty 24
Boxed items, Case Qty 48



Dura-Ball® Paint Tube Marker

- Marks with real paint, dries in 5 minutes.
 - Durable metal ball tip marks on smooth or rough surfaces.
 - Marks on metal, wood, plastic, glass, any hard surface.
 - Lead free, non-toxic.
 - Marks are weather and fade-resistant.
 - Durable metal tube with 1/8" steel ball tip.
 - All colors are low chloride making them safe for marking stainless steel
- Marking Range: -50°F to 150°F (-46°C to 66°C)

| Color | Part No. | Color | Part No. |
|--------|----------|--------|----------|
| White | 96652 | Orange | 96656 |
| Yellow | 96653 | Blue | 96657 |
| Red | 96654 | Green | 96658 |
| Black | 96655 | | |

Case Quantity 48



Valve Action® Marker

- Marks with real paint, dries in 3 minutes.
- Valve action nib releases paint as needed for continuous marking.
- Marks on all surfaces including: metal, wood, glass, plastic, rubber, cardboard and paper.
- Lead-free, low halogens.
- The fiber nib is replaceable to assure complete use of each marker.
- Durable metal barrel.
- Meets California VOC Regulations.
- Replacement tips available Part No. 96867.
- Unit packaging: 12 of one color to a box.

Marking Range: -50°F to 150°F (-46°C to 66°C)

| Color | Bulk Part No. | Carded 1/Card Part No. | Display Packs Part No. |
|-----------------------|---------------|------------------------|------------------------|
| Brown | 96809 | | |
| Purple | 96817 | | |
| White | 96820 | 96800 | 96810 |
| Yellow | 96821 | 96801 | 96811 |
| Red | 96822 | 96802 | 96812 |
| Black | 96823 | 96803 | 96813 |
| Orange | 96824 | 96807 | 96814 |
| Blue | 96825 | 96805 | 96815 |
| Green | 96826 | 96806 | 96816 |
| Gold | 96827 | | |
| Aluminum | 96832 | 96804 | 96818 |
| Lt Blue | 96835 | | |
| Assorted ² | | | 96819 |

Case Quantity 24
Bulk Case Quantity 48
² = Carded - 2/card

Cool Gel® Heat Barrier Spray

- Helps prevent heat damage to components and surrounding materials during soldering, brazing and welding.
- Unique gelled formula sticks to surfaces without dripping or running off.
- Clear, non-staining gel leaves no residue eliminating cleanup.
- Safe, non-toxic, harmless to skin and odorless.
- Thick, gelled formula requires 15 to 20 pumps for initial priming of the sprayer
- Protects painted and finished surfaces from discoloration due to adjacent torch operations.
- Case quantity: 12
- 32 oz bottle

Part No. 11509



Bloc-It® Heat Absorbing Paste

- Effectively absorbs surface heat.
- Protects adjoining surfaces that may be damaged by excessive heat.
- Safe to use: non-toxic, no asbestos, harmless to skin, and odorless.
- Easy to use: apply directly to surface from tube.
- Easy to clean: wipe off with cloth or wash with water. Leaves no stains.
- Typical uses: protects rubber and plastic components in ball, dielectric and solenoid valves during soldering; protects painted or finished surfaces from adjacent soldering, brazing or welding; prevents distortion to light gauge metals during brazing or welding.



| Part No. | Size | Case |
|----------|------------|------|
| 11511 | 10 oz tube | 24 |



Slic-Tite® Paste with Teflon*

- Heavy duty thread sealing compound.
- Use on metal, PVC, CPVC and ABS plastic pipe threads.
- Contains more Teflon* particles for greater sealing power.
- Non-toxic, non-drying and washes off hands and clothing easily.
- Sealing temperature range: -50°F to 500°F (-46°C to 260°C).
- Working pressure: 3,000 PSI (204 BAR) for Gas, 10,000 PSI (680 BAR) for liquids.
- Do not use on Oxygen service, use Teflon* tape or Oxytite® paste.
- USDA approved for use in federally-inspected meat and poultry plants.

| Part No. | Size |
|----------|----------------------------|
| 42009 | 1/4 pt brush-in-cap |
| 42019 | 1/2 pt angled brush-in-cap |

Case Quantity 24



Slic-Tite® Stik with Teflon*

- High-performance thread compound in handy stick form.
- Contains Teflon* particles for greater sealing power.
- Nontoxic, non-staining, non-drying.
- Clean-White-Washes off easily.
- Use on metal and PVC pipe thread connections for water, air, natural gas, steam, gasoline, oil, refrigerants and ammonia.
- Do not use on Oxygen service, use Teflon* tape or Oxytite® paste.

| Part No. | Size |
|----------|----------|
| 41600 | 1-1/4 oz |

Case Quantity 24

- Sealing temperature range: -50°F to +350°F (-46°C to 177°C)
- Pressures: to 5,000 PSI (340 BAR) for liquids to 500 PSI (34 BAR) for gases.



Pipe Thread Tape of Teflon*

- Standard Grade. Thickness-3 mils.
- Standard grade, low density.
- Provides a highly resistant seal on pipe threads for all types of service.
- Suitable for use with solvents, chemicals, oxygen and on food lines.
- Non-toxic.
- Permits easy disassembly, even after years of service.
- Meets Mil. Spec T-27730A.
- Sealing temperature range: -450°F to 550°F (-268°C to 288°C).
- Pressures: to 2000 PSI (136 BAR).

| Part No. | Size |
|----------|--------------|
| 44071 | 1/2" x 260" |
| 44072 | 1/2" x 520" |
| 44073 | 1/2" x 1296" |
| 44074 | 3/4" x 260" |
| 44075 | 3/4" x 520" |
| 44076 | 3/4" x 1296" |
| 44077 | 1" x 260" |
| 44078 | 1" x 520" |

Case Quantity 144



Slic-Tite® Teflon* Thread Tape

- Heavy-duty premium grade.
- Thickness-3 mils.
- High density.
- Provides a highly resistant seal on pipe threads for all types of service.
- Made in U.S.A.
- Suitable for use with solvents, chemicals, oxygen, and on food lines.
- Non-toxic.
- Permits easy disassembly, even after many years.
- Meets Mil. Spec.T-22730A.
- Sealing temperature range: -450°F to 550°F (-268°C to 288°C).
- Pressure: to 2000 PSI (136 BAR).

| Part No. | Size |
|--------------------|--------------|
| 44080 | 1/4" x 300" |
| 44081 | 1/4" x 600" |
| 44082 | 1/2" x 300" |
| 44083 | 1/2" x 600" |
| 44084 | 1/2" x 1200" |
| 44085 | 3/4" x 300" |
| 44086 | 3/4" x 600" |
| 44087 | 1" x 300" |
| 44088 | 1" x 600" |
| 44003 ¹ | 1/2" x 600" |

Case Quantity 12
Packaged in one
dozen display box

¹ Carded - 1/card



Oxytite® Pipe Thread Sealant for Oxygen

- Teflon* thread sealant for oxygen services.
- Each batch tested to ASTM G-72.
- Pressure range: to 2600 PSI (180 Bar).
- Temperature range: -320°F to 450°F (196°C to 232°C).

| Part No. | Size |
|----------|------|
| 42805 | 4 oz |

Case Quantity 6



Pipetite-Stik® Pipe Thread Compound

- Thread compound in handy stick form.
- For water, steam, air, natural gas and LP gas.
- Use on metal threads, non-toxic, lead free.
- Sealing temperature: up to 350°F (177°C).
- Pressures: to 2000 PSI (136 Bar) for liquids to 350 PSI (24 BAR) for gases.
- Certified by NSF to meet ANSI/NSF Std. 62 for use on potable water.
- Classified by Underwriters Laboratories, U.S.A.
- Cleans up with soap and water.

| Part No. | Size | Case |
|----------|----------|------|
| 11175 | 1-1/4 oz | 144 |
| 11176 | 4 oz | 72 |

One dozen display pack

NOTE: Do not use on oxygen service

* DuPont Registered Trademark

Anti-Seize Compounds / Temperature Indicators



E-Z Break®-Copper Grade

- Copper-based anti-seize and lubricating compound.
- Resists rust and corrosion.
- Recommended for coating nuts, bolts, valves, flanges, splines for easy break out after years of service.
- Meets Mil. Spec. Mil. A-907E.
- Authorized by USDA for use in federally inspected meat and poultry plants. Temperature: to 1800°F (982°C).

| Part No. | Size | Case |
|----------|--------------------------|------|
| 08900 | 1 oz tube-display pk | 24 |
| 08910 | 10 oz angle brush-in-cap | 24 |
| 08916 | 14 oz aerosol | 12 |
| 08907 | 16 oz angle brush-in-cap | 24 |



E-Z Break®-Nickel Grade

- Contains fine particles of nickel and other additives.
- Contains no copper.
- Resists rust and corrosion.
- Makes disassembly easy, even after years of service.
- Temperature: to 2600°F (1427°C).
- Helps prevent galling of stainless steel threads.

| Part No. | Size | Case |
|----------|--------------------------|------|
| 08971 | 8 oz angle brush-in-cap | 24 |
| 08972 | 16 oz angle brush-in-cap | 24 |

Thermomelt® Heat Stik™ Temperature Indicators

- Accurate, fast, low-cost method for measuring surface temperatures.
- Accurate to within $\pm 1\%$ of stated temperature.
- 4-1/2" Thermomelt® Big Stik® features a stainless steel holder with pocket clip for convenient, easy use.
- Meets ANSI/ASME CODE B31 & B31.3, AWS D1.1 and ASME Code Sec. I, III and VII, NIST traceable.

| TYPE | SIZE |
|-----------------------|--|
| THERMOMELT® BIG STIK® | 4-1/2" size features stainless steel holder & pocket clip. |

33% Bigger than the original



| Temperature | | | Temperature | | | Temperature | | |
|-------------|-----|----------|-------------|-----|----------|-------------|------|----------|
| °F | °C | Part No. | °F | °C | Part No. | °F | °C | Part No. |
| 100 | 38 | 86400 | 313 | 156 | 86643 | 900 | 482 | 86904 |
| 109 | 43 | 86409 | 319 | 159 | 86652 | 950 | 510 | 86922 |
| 113 | 45 | 86418 | 325 | 163 | 86661 | 1000 | 538 | 86931 |
| 119 | 48 | 86427 | 331 | 166 | 86670 | 1022 | 550 | 86940 |
| 125 | 52 | 86436 | 338 | 170 | 86679 | 1050 | 565 | 86949 |
| 131 | 55 | 86445 | 344 | 173 | 86688 | 1100 | 593 | 86958 |
| 138 | 59 | 86454 | 350 | 177 | 86697 | 1150 | 621 | 86967 |
| 150 | 66 | 86463 | 363 | 184 | 86706 | 1200 | 649 | 86976 |
| 163 | 73 | 86472 | 375 | 191 | 86715 | 1250 | 677 | 86985 |
| 175 | 79 | 86481 | 388 | 198 | 86724 | 1300 | 704 | 86994 |
| 182 | 83 | 86490 | 400 | 204 | 86733 | 1350 | 732 | 87003 |
| 188 | 87 | 86499 | 413 | 212 | 86742 | 1400 | 760 | 87012 |
| 194 | 90 | 86508 | 425 | 218 | 86751 | 1425 | 774 | 87021 |
| 200 | 93 | 86517 | 438 | 225 | 86760 | 1450 | 788 | 87030 |
| 206 | 97 | 86522 | 450 | 232 | 86769 | 1480 | 804 | 87039 |
| 213 | 101 | 86526 | 463 | 239 | 86778 | 1500 | 816 | 87048 |
| 219 | 104 | 86535 | 475 | 246 | 86787 | 1550 | 843 | 87057 |
| 225 | 107 | 86544 | 488 | 253 | 86796 | 1600 | 871 | 87066 |
| 238 | 114 | 86553 | 500 | 260 | 86805 | 1650 | 899 | 87075 |
| 250 | 121 | 86562 | 525 | 274 | 86814 | 1700 | 927 | 87084 |
| 256 | 124 | 86569 | 550 | 288 | 86823 | 1750 | 954 | 87093 |
| 263 | 128 | 86571 | 575 | 302 | 86832 | 1800 | 982 | 87102 |
| 269 | 132 | 86580 | 600 | 316 | 86841 | 1850 | 1010 | 87111 |
| 275 | 135 | 86589 | 625 | 329 | 86850 | 1900 | 1038 | 87120 |
| 282 | 139 | 86598 | 650 | 343 | 86859 | 1950 | 1065 | 87129 |
| 288 | 142 | 86607 | 700 | 371 | 86868 | 2000 | 1093 | 87138 |
| 294 | 146 | 86616 | 750 | 399 | 86877 | 2050 | 1121 | 87147 |
| 300 | 149 | 86625 | 800 | 427 | 86886 | 2100 | 1149 | 87156 |
| 306 | 152 | 86634 | 850 | 454 | 86895 | 2150 | 1177 | 87165 |
| | | | | | | 2200 | 1204 | 87174 |

Thermomelt® Belt Holster

- Holds 3 Thermomelt® Heat Stiks™ or industrial markers.
- Dispenses easily with gloved hand.
- Ships 12 holsters/case

Part No. 68608



Thermomelt® Push Button Holder

- Advances and retracts easily with one finger.
- Prevents breaking.
- Ships 12 holders/case

Part No. 85002





Pro-Line™ Paint Markers

- Available in fine (2 mm) and micro (1 mm) Tip sizes for ultimate precision.
- High-strength, lightweight barrel for industrial use.
- Ideal for metal, also suitable for wood, glass, plastic, rubber and more.
- Xylene-free for less odor.
- Self-storing cap with integrated pocket clip.
- Ergonomic design for comfortable extended use.

Fine - 2 mm

| Part No. | Color | Qty |
|----------|-----------|-----|
| Bulk | | |
| 96871 | White | 48 |
| 96872 | Yellow | 48 |
| 96873 | Black | 48 |
| 96874 | Red | 48 |
| 96875 | Blue | 48 |
| 96876 | Green | 48 |
| 96877 | Orange | 48 |
| 96878 | Pink | 48 |
| 96879 | Lt. Green | 48 |
| Carded | | |
| 96857 | White | 24 |
| 96858 | Yellow | 24 |
| 96859 | Red | 24 |
| 96860 | Black | 24 |
| 96861 | Assorted | 24 |

| Part No. | Color | Qty |
|------------------|----------|-----|
| Canister Display | | |
| 96862 | White | 48 |
| 96863 | Yellow | 48 |
| 96864 | Red | 48 |
| 96865 | Black | 48 |
| Acrylic Display | | |
| 96887 | Assorted | 96 |

Micro - 1 mm

| Part No. | Color | Qty |
|----------|--------|-----|
| Bulk | | |
| 96888 | White | 48 |
| 96889 | Yellow | 48 |
| 96890 | Black | 48 |
| 96891 | Red | 48 |

| Part No. | Color | Qty |
|------------------|----------|-----|
| Carded | | |
| 96892 | White | 24 |
| 96893 | Yellow | 24 |
| 96894 | Black | 24 |
| 96895 | Red | 24 |
| Canister Display | | |
| 96879 | Assorted | 48 |



Pro-Max™ Paint Markers

- Super sized 1/2" + nib for highly visible marks.
- High-strength, lightweight barrel for industrial use.
- Ideal for identification, fill-in marking, signage, safety marking on any surface.
- Available in six ultra-visible colors.
- Xylene-free for less odor.
- Self-storing cap.

| Part No. | Color | Qty |
|-----------------|----------|-----|
| Bulk | | |
| 90900 | White | 24 |
| 90901 | Yellow | 24 |
| 90902 | Red | 24 |
| 90903 | Black | 24 |
| 90904 | Orange | 24 |
| 90905 | Blue | 24 |
| Acrylic Display | | |
| 96897 | Assorted | 24 |